



## SPARE PARTS FOR THE STYLE 3SC (3S)

**TRIM KIT:** The Trim Kit includes a Retainer, Poppet, Spring, and Poppet O-Ring & 2 Body O-Rings.

**O-RING KIT:** The O-ring Kit includes 3 Poppet O-Rings and 6 Body O-Rings. 3A compliant O-Rings include EPDM (3E), Viton (3V), and Silicone (3S).

**POPPET:** Includes 1 Poppet, no additional components

**RETAINER:** Includes 1 Retainer, no additional components

**SPRING:** Includes 1 Spring, no additional components

Please use the table below as a guideline for part numbering

Nominal Line Size	Trim Kit Part Number	O-Ring Kit Part Number	Poppet Part Number	Retainer Part Number	Spring Part Number
1	TKHSS <u>XX</u> YYYY	OKH <u>XX</u>	%3PTHSSA	%3RTHSSA	%3SH <u>YYYY</u> SS
1 1/2	TKJSS <u>XX</u> YYYY	OKJ <u>XX</u>	%3PTJSSA	%3RTJSSA	%3SJ <u>YYYY</u> SS
2	TKKSS <u>XX</u> YYYY	OKK <u>XX</u>	%3PTKSSA	%3RTKSSA	%3SK <u>YYYY</u> SS
2 1/2	TKLSS <u>XX</u> YYYY	OKL <u>XX</u>	%3PTLSSA	%3RTLSSA	%3SL <u>YYYY</u> SS
3	TKMSS <u>XX</u> YYYY	OKM <u>XX</u>	%3PTMSSA	%3RTMSSA	%3SM <u>YYYY</u> SS
4	TKNSS <u>XX</u> YYYY	OKN <u>XX</u>	%3PTNSSA	%3RTNSSA	%3SN <u>YYYY</u> SS

Fill in XX for desired o-ring material. Fill in YYYY with desired spring cracking pressure in PSI.

**NOTE:** Standard springs are .500-PSI & 1.50-PSI (other settings are available).

The special order charge will apply on non-standard springs that have to be special ordered.

Consult factory to determine if your desired setting can be designed and supplied.

Standard finish on all components is 32RA or better. Finer finishes are available.

**SERVING CUSTOMERS AROUND THE WORLD FOR OVER 50 YEARS!**