



NOTES:

1. INLET: CO2 FITTING WITH CGA 320 NUT
2. OUTLET: 5/16" BARB SHUTOFF WITH CHECK
3. GAUGES: 160# AND 2000#
4. SAFETY BLOW-OFF: 130 ± 4 PSI
5. WORKING PRESSURE: 0-120 PSI
6. POLY BONNET WITH RED ADJ CAP

MATERIAL	NAME	DATE
	DRAWN	JPK 07/07/10
FINISH	ENG APPR.	
	PROPRIETARY AND CONFIDENTIAL	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2° BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.		



TITLE: **REG, PRI, 160#, TANK FTG, 5/16B-CV SHUTOFF, 2000#, POLY, RED**

SIZE	DWG. NO.	REV
A	T5741PMHPT_SALES	A

SCALE: 1:2 DO NOT SCALE DRAWING SHEET 1 OF 1