

## Safety Pop-Off Valves

### Applications:

- for use on compressors and in compressed air service

### Features:

- designed to protect un-fired pressure vessels from over-pressure
- ASME Code, National Board Certified
- CSA B51-03 certified
- maximum temperature: **400°F (204°C)**

### Soft Seat Safety Pop-Off Valves

#### Feature:

- constructed of precision machined brass bar stock with a silicone disc sealing on the brass



¼" male NPT

Preset Pressure PSI	SCFM	Brass	
		Part #	Price/E
100	51	<b>KSV10-100</b>	<b>\$16.40</b>
125	62	<b>KSV10-125</b>	<b>16.40</b>
150	73	<b>KSV10-150</b>	<b>16.40</b>
175	84	<b>KSV10-175</b>	<b>16.40</b>

### Standard Safety Pop-Off Valves

#### Features:

- brass valves are supplied with a stainless steel ball
- stainless valves are all stainless construction with a soft seat



¼" male NPT

Preset Pressure PSI	Brass		SCFM	Stainless Steel		SCFM
	Part #	Price/E		Part #	Price/E	
30	<b>SV30</b>	<b>\$35.75</b>	35	<b>SV30SS</b>	<b>\$198.00</b>	35
100	<b>SV100</b>	<b>35.75</b>	89	<b>SV100SS</b>	<b>198.00</b>	92
125	<b>SV125</b>	<b>35.75</b>	109	<b>SV125SS</b>	<b>198.00</b>	112
150	<b>SV150</b>	<b>35.75</b>	129	<b>SV150SS</b>	<b>198.00</b>	132
175	<b>SV175</b>	<b>35.75</b>	149	<b>SV175SS</b>	<b>198.00</b>	153
200	<b>SV200</b>	<b>35.75</b>	168	<b>SV200SS</b>	<b>198.00</b>	173

### Heavy Duty, High Capacity Safety Pop-Off Valves

#### Feature:

- all brass construction with stainless steel ball on a precision machined brass seat



½" male NPT

Preset Pressure PSI	SCFM	Brass	
		Part #	Price/E
30	73	<b>SV30HD<sup>1</sup></b>	<b>\$84.20</b>
100	208	<b>SV100HD</b>	<b>84.20</b>
125	254	<b>SV125HD</b>	<b>84.20</b>
150	300	<b>SV150HD</b>	<b>84.20</b>
175	346	<b>SV175HD</b>	<b>84.20</b>
200	391	<b>SV200HD</b>	<b>84.20</b>

<sup>1</sup> constructed with soft seat